



2015 XF 6000 Sno Pro



AVAILABLE COLORS



Engine Specifications

Type	2-stroke
Displacement	599cc
Cooling	Liquid
Cylinders	2
Bore x Stroke	73.8 x 70 mm
Lubrication	Electronic injection
Ignition	3D sequential fire, throttle position sensor
Carburetion	47 mm dual throttle body batteryless EFI
Exhaust	APV with tuned pipe, pipe sensor and stainless steel muffler
Fuel Capacity	11.7 gal.

Suspension Specifications

Front Suspension	Arctic Race Suspension with FOX FLOAT 3 shocks and sway bar
Front Travel	10 in.
Rear Suspension	Slide-Action Suspension with tri-hub rear axle system, coupling blocks, Torque-Sensing Link, adjustable torsion springs, Arctic Cat (IFP) shocks (2" dia. rear shock)
Rear Travel	13.5 in.

Powertrain Specifications

Drive Clutch	Arctic 6 post (rpm sensing)
Driven Clutch	10.75 in. dia. Arctic (roller cam)
Drive System	Arctic Drive System
Brakes	Race radial master cylinder hydraulic brake

Dimensions Specifications

Overall Length	125.75 in.
Overall Width	47.75 in.
Ski Stance	42-43 in. adjustable
Ski Type	Trail 6 in.
Runner Type	Dual skag w/carbide
Track Type	Ripsaw II
Track Width	15 in.
Track Length	137 in.
Lug	1.25 in.
Pitch	2.86 in.

Standard Features

Push-button engine reverse, dual halogen headlight (2-bulb), front bumper, adjustable handlebar, deluxe digital gauge, electric gas gauge, low oil light, coolant overheat light, coolant temp, intake air temp, battery voltage, low fuel light, clock, high/low hand & thumb warmers, accessory outlet, race-height windshield, electric start, belt bag, air pump

Optional Features

2-up seat, tank pads, (ex low, flyscreen, mid, high) windshield, mirrors, rack, hitch, tether switch, hand guards, front sport bumper, premium shocks, storage bag

Specifications Subject To Change

All rights reserved. Cobra,™ Hacksaw™ and Ripsaw™ are trademarks of Camoplast Inc. Diamond Direct Drive™ is a trademark of Black Diamond, Inc. FOX EVOL,™ FOX FLOAT™ and FOX Zero Pro are registered trademarks of FOX Racing Shox. ACT™ Arctic Cat, Arctic Drive System,™ Arctic Race Suspension,™ ARS,™ AWS,™ Bearcat, C-TEC2,™ C-TEC4,™ CatMaster, Cat to the Core,™ Cross Country,™ El Tigré, FasTrack, High Country,™ Lynx, Pantera, Power Claw,™ ProClimb,™ ProCross,™ ProTour,™ RIDEMORE,™ Share Our Passion,™ Slide-Action Rear Suspension,™ Sno Pro, SpeedRack, Torque Control Link,™ Twin Spar,™ World's Fastest Snowmobiles,™ XT,™ Z1™ and ZR are trademarks or registered trademarks of Arctic Cat Inc. Arctic Cat Sales Inc. is not a successor of Arctic Enterprises, Inc. ©2014 Arctic Cat Sales Inc., 601 Brooks Avenue South, Thief River Falls, MN 56701.

At Arctic Cat, we're always improving our snowmobiles to provide the best performance and experience. That's why the specifications for 2015 model Arctic Cat snowmobiles are subject to change without notice. See your dealer for details.

*MSRP excludes tax, license, registration, destination charge of \$400 and dealer setup. Dealer prices may vary.