




## 2016 ZR 9000 Limited (129)



### AVAILABLE COLORS



Team Arctic Green

### Engine Specifications

Type	4-stroke
Displacement	1056cc
Cooling	Liquid
Cylinders	2-Turbocharged
Bore x Stroke	98 x 70 mm
Lubrication	Dry sump
Ignition	Full transistor
Fuel Delivery	Electronic Fuel Injected (EFI)
Exhaust	Turbocharger with stainless steel muffler
Fuel Capacity	10.4 gal.
Minimum Octane	91

### Suspension Specifications

Front Suspension	Arctic Race Suspension with sway bar
Ski Shocks	FOX 1.5 ZERO QS3
Front Travel	10 in.
Rear Suspension	SLIDE-ACTION Rear Suspension with tri-hub rear axle system, coupling blocks, Torque-Sensing Link rear arm and adjustable torsion springs
Front Track Shock	Arctic Cat Gas IFP
Rear Track Shock	FOX 2.0 ZERO QS3
Rear Travel	13.5 in.

### Dimensions Specifications

Overall Length	121 in.
Overall Width	47.75 in.
Track Type	Ripsaw
Track Width	15 in.
Track Length	129 in.
Lug	1.25 in.
Pitch	2.86 in.
Ski Stance	42-43 in. Adjustable
Ski Type / Width	ProCross - 6 in.
Runner Type	Dual deep split runner w/carbide

### Instrumentation Specifications

Type of Gauge	Deluxe Digital Analog
Speedometer	Digital/Analog
Tachometer	Digital/Analog
Odometer	Digital
Fuel	Digital
Oil	Indicator Light
Coolant	Indicator Light
Clock	Digital
Battery Voltage	Digital
Hours	Digital

### Feature Specifications

12V Outlet	Standard
Electric Start	Standard
Front Bumper	ProCross
Goggle Holder	Standard
Hand & Thumb Warmers	Standard
Headlights	Dual halogen 2-bulb
Heated Drivers Seat	Standard
Ice Scratchers	Accessory
Lightweight Brake Disc	Accessory
Mirrors	Accessory
Mountain Strap	Accessory
Rear Rack	Accessory
Rear Storage	Tunnel Bag
Seat	High Performance
Side Panel Wind Deflectors	Accessory
Sno Pro Brake Lever	Standard
Steering	5.5" fixed riser with adjustable handlebar
Tether Switch	Accessory
Tow Hitch	Accessory
Tunnel Flare	Standard
Visor Plug-ins	Accessory
Windshield	11" Mid-height

### Powertrain Specifications

Drive Clutch	TEAM Rapid Response
Driven Clutch	TEAM Rapid Reaction BOSS
Drive System	Arctic Drive System
Brakes	Race radial master cylinder hydraulic brake
Clutch Calibration	0-5,000 ft.
Gearing	21/38
Reverse	Push-button

Specifications Subject To Change

All rights reserved. Cobra,™ Hacksaw™ and Ripsaw™ are trademarks of Camoplast Inc. Diamond Direct Drive™ is a trademark of Black Diamond, Inc. FOX EVOL,™ FOX FLOAT™ and FOX Zero Pro are registered trademarks of FOX Racing Shox. ACT™ Arctic Cat, Arctic Drive System,™ Arctic Race Suspension,™ ARS,™ AWS,™ Bearcat, C-TEC2,™ C-TEC4,™ CatMaster, Cat to the Core,™ Cross Country,™ El Tigré,™ FasTrack,™ High Country,™ Lynx,™ Pantera,™ Power Claw,™ ProClimb,™ ProCross,™ ProTour,™ RIDEMORE,™ Share Our Passion,™ Slide-Action Rear Suspension,™ Sno Pro,™ SpeedRack,™ Torque Control Link,™ Twin Spar,™ World's Fastest Snowmobiles,™ XT,™ Z1™ and ZR™ are trademarks or registered trademarks of Arctic Cat Inc. Arctic Cat Sales Inc. is not a successor of Arctic Enterprises, Inc. ©2014 Arctic Cat Sales Inc., 601 Brooks Avenue South, Thief River Falls, MN 56701.

At Arctic Cat, we're always improving our snowmobiles to provide the best performance and experience. That's why the specifications for 2015 model Arctic Cat snowmobiles are subject to change without notice. See your

dealer for details.

\*MSRP excludes tax, license, registration, destination charge of \$400 and dealer setup. Dealer prices may vary.